

MDS-250A Series

Highlights & Features

- Safety Approvals to IEC 60601-1 3.1rd ed. & IEC 62368-1
- Compliant with IEC 60601-1-2 4th Ed. Requirements
- Up to 150 Watt Convection
- Up to 500 K Hrs MTBF
- Suited for Type BF Medical Products
- 2 × MOPP isolation



Safety Standards



CB Certified for worldwide use

Model Number: MDS-250A
Unit Weight: 405 g (MDS-250APB24)
 610 g (MDS-250ADB24)

Dimensions (L x W x H):
 127.3 x 76.5 x 36.6 mm 5 x 3 x 1.44 inch (MDS-250APB24)
 140.0 x 127.3 x 44.4 mm 5.5 x 3.5 x 1.75 inch (MDS-250ADB24)

General Description

Delta's new MDS-250APB24 open frame design offers a high energy density (12 Watts/in³) 3 x 5 inch design for Type BF patient access medical products. With operating parameters of 90 to 264 Vac universal input voltage, temperatures of -10 to +70 degrees centigrade, and altitudes of up to 5,000 meters (16,400 feet), the design is well suited for a variety of both medical and non-medical applications. Other features include input surge of 300 Vac, low leakage current, no-load input power < 0.5 Watt, and 500K hour MTBF. This product is certified for EMC standards EN/BS EN 55011 for industrial, scientific and medical (ISM) radio-frequency equipment, and EN/BS EN 55032 for Industrial Technology Equipment (ITE) radio-frequency equipment.

An enhanced feature set, includes a 5 Volt/0.5 amp standby output, remote on/off, remote sense, and a power good signal that are included as part of the standard product.

The design, which has protection against shock compliant with 2XMOPP and Type BF requirements, has both medical (with risk report available), and ITE safety approvals, including cURus (US & Canada) /TUV/GB (China); plus, CB certificates with all national deviations. Full compliance with RoHS Directive for environmental protection is included. The unit comes in a standard 3 x 5 inch footprint, with height suitable for 1U applications. Robust terminals are capable of multiple connections of the main output to the end product. Enclosed assembly is available option.

Model Information (All with 5V/0.5A standby available)

| Model Number | Input Voltage | Output Voltage | Convection Current Output | Forced Air Current Output |
|-------------------------------|---------------|----------------|---------------------------|-----------------------------------|
| MDS-250APB24 | 90-264 Vac | 24 Vdc | 0-6.25 A | 0-10.41 A(with 10 CFM forced air) |
| MDS-250ADB24 (Enclosed cover) | 90-264 Vac | 24 Vdc | 0-5.62 A | 0-10.41 A(with 10 CFM forced air) |

Model Numbering

| | | | | | | |
|----------------------------|---|----------------------|--|------------------------------------|-------------------------------|--|
| MDS | 250 | A | □ | B | 24 | □□ |
| Delta Medical Power Supply | Max wattage in the product series. 250 → 250 W | Family Code A ~ Z | Product Type P: Open Frame D: Enclosed | Input Type Code B: 3pin Class I | Output Voltage 24 for 24 V | AA: With Remote On/Off AB: Without Remote On/Off Refer to page 9 |

Specifications

Input Ratings / Characteristics

| | |
|--|---|
| Nominal Input Voltage | 100-240 Vac |
| Input Voltage Range | 90-264 Vac |
| Nominal Input Frequency | 50-60 Hz |
| Input Frequency Range | 47-63 Hz |
| Input Current (max) | 3.5 A |
| Input Surge Voltage (max) | 300 Vac for 100 ms |
| Full load Efficiency (typ.) | 91.85% @ 115 Vac/60 Hz 92.98% @ 230 Vac/50 Hz, Reference Fig. 1 |
| Standby Power (max) | 0.5 W (Inhibit signal high, 24 volt turned off) @ 115 Vac/60 Hz, 230 Vac/50 Hz |
| Inrush Current (max) | 40 A @ 230 Vac, cold start |
| Input-PE (protective earth) leakage current (max) | 0.1 mA @ NC ¹⁾ , 0.3 mA @ SFC ¹⁾ |
| Output-PE (protective earth) leakage current for Type BF application (max) | 0.1 mA @ NC ¹⁾ , 0.5 mA @ SFC ¹⁾ |
| Power Factor (min) | 0.9 @ 115 V/50 Hz, 230 V/50 Hz, full load |

1) NC: normal condition, SFC: single fault condition

Leakage Current

| Input-PE Leakage Current | 100 Vac/60 Hz (Typ) | 264 Vac/60 Hz (Typ) | Delta Limit | IEC60601-1 Limit |
|---|---------------------|---------------------|-------------|------------------|
| Normal Condition | 17.4 uA | 43.3 uA | 100 uA max | 5000 uA max |
| Single Fault Condition | 32.7 uA | 90.6 uA | 300 uA max | 10000 uA max |
| Output-PE Leakage Current for Type BF application | | | | |
| Normal Condition | 28.3 uA | 86.6 uA | 100 uA max | 100 uA max |
| Single Fault Condition | 42.8 uA | 128.4 uA | 500 uA max | 500 uA max |





Fig. 1 Efficiency versus output load

Output Ratings / Characteristics (Main Output)

| | |
|---|---|
| Nominal Output Voltage (Vrated) | 24 V |
| Total Regulation | ±3% |
| Output Power | 250 W 10 CFM air, up to 150 W convection air |
| Line Regulation (max) | ±0.5% |
| Load Regulation (max) | ±1% |
| Ripple & Noise (typ.) | 1% pk-pk Vrated @ 250 W load, (Refer to Fig. 2 & Fig. 3) |
| Start-up Time (max) | 2000 ms @ 115Vac |
| Hold-up Time (min) | 10 ms @ 100 Vac and 115 Vac, with 250 W load 20 ms @ 100 Vac and 115 Vac, with 130 W load |
| Dynamic Response (Overshoot & Undershoot O/P Voltage) | ± 5% @ with 50-100% load change |
| Capacitive load (max) | 1500 uF |
| Rise time (max) | 100 ms |
| Remote Sense | Up to 500 mV compensation for voltage drop across external wire connections to load. Short and reverse connection protected. |

Output Ratings / Characteristics—Standby Output

| | |
|---|---------------------------------------|
| Nominal Output Voltage of standby output (Vrated) | 5 V |
| Total Regulation of standby output | ±3% |
| Ripple & Noise of standby output | 100 mV max (Refer to Fig. 2 & Fig. 3) |



(a) 115 V (measured value=138.0 mV for 24 V and 35.0 mV for 5 V) (b) 230 V (measured value=144.0 mV for 24 V and 26.6 mV for 5 V)

Fig.2 Ripple & Noise example, 20 MHz BW




Fig. 3 Ripple & Noise measurement circuit



Mechanical

| | | |
|------------------------|------------------------------|--|
| Case Cover | | Enclosed, refer to drawings on pages 8 and 9 |
| Dimensions (L x W x H) | MDS-250APB24 MDS-250ADB24 | 127.3 x 76.5 x 36.6 mm (5 x 3 x 1.44 inch) 140.0 x 88.9 x 44.4 mm (3.5 x 5.5 x 1.75 inch) |
| Unit Weight | MDS-250APB24 MDS-250ADB24 | 405 g (0.89 lb.) 610 g (1.34 lb.) |

Environment


| | | |
|-----------------------------|-----------|---|
| Surrounding Air Temperature | Operating | Absolute Maximum/Minimum Rating. -10°C to +70°C. Linearly derate from 100% load at 50°C to 45 ~ 50% load at 70°C Note: see power de-rating curves below |
| | Storage | -40°C to +85°C |
| Operating Humidity | | 5-95% RH (Non-Condensing) |
| Operating Altitude | | 5,000 meters (16,400 feet or 50 kPa) |
| Non-operating Altitude | | 5,000 meters (16,400 feet or 50 kPa) |
| Shock Test (Non-Operating) | | 50 G, 11ms, 3 shocks for each direction |
| Vibration (Operating) | | 5-500 Hz, 2 Grms, 15 minute for each three axis |

Power De-rating curves




Load De-rating Fixture and Test Setup. Fan is DELTA Part Number AFB0512HHD.

MDS-250APB24 Open frame model



MDS-250ADB24 Enclosed cover model



Protections (for both 24 Volt and 5 Volt Standby outputs, unless otherwise indicated)

| | |
|--------------------------------|--|
| Overvoltage (max) | Main output 125% of rated voltage, Latch Mode Standby Output 125% of rated voltage, Latch Mode |
| Over load / Over current (max) | Main output 200% of rated current Standby Output 1.06 A max Hiccup Mode(Non-Latching, Auto-Recovery) |
| Over Temperature | Latch Mode for main output |
| Short Circuit | Hiccup Mode, (Non-Latching, Auto-Recovery) |

Reliability Data

| | | |
|---|---------------------|-------------------------------------|
| MTBF (Minimum) at 115 Vac, 150 W, 35 °C | Convection Air Flow | 500 Khrs based on Telecordia SR-332 |
| Operating life (Minimum) at 115 Vac, 150 W, 25°C | Convection Air Flow | 26,280 hrs |

Safety Standards / Directives

| | | |
|--------------------|---|--|
| Medical Safety | IEC 60601-1 2 nd , 3 rd and 3.1 rd edition CB report IEC 60601-1 edition 3.1 rd (2012), EN 60601-1 (2006) + A11 + A1 + A12, CAN/CSA-C22.2 NO. 60601-1:14, ANSI/AAMI ES 60601-1:2005/(R) 2012 | |
| ITE Safety | IEC 60950-1, IEC 62368-1 CB report TUV 60950-1 UL 60950-1+CAN/CSA 60950-1 CCC GB 17625.1; GB 4943.1; GB/T 9254.1 | |
| CE | In conformance with EMC Directive 2014/30/EU and Low Voltage Directive 2014/35/EU EN 60601-1: 2006 + A11: 2011 + A1L 2013 + A12: 2014 & EN 60601-1-2: 2015 | |
| UKCA | In conformance with Electrical Equipment (Safety) Regulations 2016 and Electromagnetic Compatibility Regulations 2016, Medical Devices Regulations 2002 (UK MDR 2002) | |
| Galvanic Isolation | Input to/Output (2XMOPP) Input to/Ground (1XMOPP) Output to/Ground | 4000 Vac 1500 Vac ¹⁾ 1500 Vac (Type BF application rated) |

1) PSU can support PoE applications with Primary to FG 2500 Vac test.


EMC (Compliant with IEC-60601-1-2 4th Ed. requirements)

| | | |
|-----------------------------------|----------------|--|
| EMC / Emissions | | EN/BS EN 55011, EN/BS EN 55032, FCC Title 47:Class |
| Harmonic Current Emissions | IEC 61000-3-2 | Meet Class D limit |
| Voltage Flicker | IEC 61000-3-3 | |
| Immunity to | | |
| Electrostatic Discharge | IEC 61000-4-2 | Level 4 Criteria A ¹⁾ Air Discharge: 15 kV Contact Discharge: 8 kV |
| Radiated Field | IEC 61000-4-3 | Criteria A ¹⁾ 80 MHz-2700 MHz, 10 V/m AM modulation 385 MHz-5785 MHz, 28 V/m Pulse mode and other modulation |
| Electrical Fast Transient / Burst | IEC 61000-4-4 | Level 3 Criteria A ¹⁾ : 2 kV |
| Surge | IEC 61000-4-5 | Level 3 Criteria A ¹⁾ Common Mode ³⁾ : 2 kV Differential Mode ⁴⁾ : 1 kV |
| Conducted | IEC 61000-4-6 | Level 2 Criteria A ¹⁾ 150 kHz-80 MHz, 3Vrms, 6 Vrms at ISM bands and Amateur radio bands |
| Power Frequency Magnetic Fields | IEC 61000-4-8 | Criteria A ¹⁾ Magnetic field strength 30 A/m |
| Voltage Dips | IEC 61000-4-11 | Criteria B ¹⁾ 0% U _T , 0.5 cycle (10 ms), 0°/45°/90°/135°/180°/225°/270°/315°/360° Criteria B ²⁾ (Criteria A ¹⁾ with 130W load) 0% U _T , 1 cycle (20 ms), 0° Criteria B ²⁾ 70% U _T , 25 cycle (500 ms), 0° Criteria B ²⁾ 0% U _T , 250 cycle (5000 ms), 0° |


1) Criteria A: Normal performance within the specification limits.
2) Criteria B: Output out of regulation, or shuts down during test. Automatically restore to normal operation after test.
3) Asymmetrical: Common mode (Line to earth)
4) Symmetrical: Differential mode (Line to line)
5) Unless otherwise noted, requirements apply at 250 watt output load

Dimensions

Open Frame Mechanical drawing (MDS-250APB24)



Covered Enclosure Mechanical drawing (MDS-250ADB24)



Notes

- Dimensions are in mm(inches)
- There are two locations where assembled power supply is connected to the customer's product
 - a. Bottom mounting, use (4X) M3 screws to affix assembled power supply to product's enclosure. Extruded hole with thread must be withstand 9 Kgf.cm (7.81 lb-in) min. Maximum allowed screw penetration is 3.5 mm (0.138 inch).
 - b. Side mounting, use (2X) M3 screws to affix one side of assembled power supply to the product's enclosure. Extruded hole with thread must be withstand 9 Kgf.cm (7.81 lb-in) min. Maximum allowed screw penetration is 3.5 mm (0.138 inch).

- CN1 mates with Molex housing 26-03-4030 and Molex series 6838 crimp terminals. Input Line can also be connected to Input Neutral, and Input Neutral can be connected to Input Line.
- CN102 & CN103(Output Connector) : Cross recessed pan head screws M3X0.5x10, with spring washers and flat washers, force required to tighten the screws is 7~8 kgf.cm(6.1~7.0 inch-lb)
- CN2 : PINGOOD JP-13T or equivalent mates with KST:FDNYD1-187 or other applicable connectors.
- CN101 mates with JST housing SHR-10V-S-B & SHR-10V-S and JST SSH-003T-P0.2-H crimp terminals.

| Control and STANDBY connector CN101 | |
|-------------------------------------|---------------------------------|
| Pin 1 | Remote sense + |
| Pin 2 | Remote sense – |
| Pin 3 | Power Good + |
| Pin 4 | Power Good -(DC RTN) |
| Pin 5 | Remote ON_OFF/INHIBIT + |
| Pin 6 | Remote ON_OFF/INHIBIT -(DC RTN) |
| Pin 7 | 5V Standby |
| Pin 8 | DC RTN |
| Pin 9 | 5V Standby |
| Pin 10 | DC RTN |

For optimum EMI performance, the two mounting points shown in open frame mechanical drawing need to be connected together to system earth case. Protective bonding conductor from the end product protective earth terminal can be tied to CN2 for open frame model. CN2 of enclosed model is connected to the cover by assembly screws already; in this case, system protective earth connection can be connected to the cover or to CN2

| MDS-250APB24 □□ | |
|-----------------|--|
| <u>AA</u> | Delta Standard – With Remote On/Off |
| <u>AB</u> | Without Remote On/Off A mating connector with JST housing SHR-10V-S-B & SHR-10V-S and JST SSH-003T-P0.2-H terminals, with jumper wire between pins 5 and 6, will be inserted into CN101. This will allow the power supply to turn on, without user intervention, upon the application of input AC voltage Due to presence of mating connector, external connections cannot be made to pins 1-10 of CN101. |
| MDS-250ADB24 □□ | |
| <u>AA</u> | Delta Standard – With Remote On/Off |

Functions

Start-up Time

The time required for the output voltage to reach 90% of its final steady state value, after the input voltage is applied.


Rise Time

The time required for the output voltage to change from 10% to 90% of its final steady state value.

Hold-up Time

Time between the collapse of the AC input voltage, and the output falling to 90% of its steady state value.


■ Graph illustrating the Start-up Time, Rise Time, and Hold-up Time



Dynamic Response (24 Volt Output)


The power supply output voltage will remain within $\pm 5\%$ of its steady state value, when subjected to a dynamic load 50 to 100% of its rated current.

■ 50 to 100% Load



Inrush Current

Inrush current is the input current that occurs when the input voltage is first applied. For AC input voltages, the maximum peak value of inrush current will occur during the first half cycle of the applied AC voltage. This peak value decreases exponentially during subsequent cycles of AC voltage.




Overvoltage Protection

The power supply's overvoltage circuit will be activated when its internal feedback circuit fails. The output voltage shall not exceed its specifications defined on Page 6 under "Protections". Power supply will latch off, and require removal/re-application of input AC voltage in order to restart.

Overload & Over current Protections

The power supply's Overload (OLP) and Over current (OCP) Protections will be activated before the 24 volt outputs' current exceeds 160% of IO (Max load). Upon such an occurrence, VO will start to drop. Once the power supply has reached its maximum power limit, the protection will be activated and the power supply will go into "Hiccup mode" (Auto-Recovery). The power supply will recover once the fault condition causing the OLP and OCP is removed and IO is back within the specified limit. For the standby output, the performance is the same, with the exception that the protection will be activated before the output current exceeds 1.06 amps.



Additionally, if the 24 Volts' out is $>100\%$; but $<160\%$ for a prolonged period of time (depending on the load), the Over Temperature Protection (OTP) will be activated due to high temperature on critical components. The power supply will then go into latch mode.

Short Circuit Protection


The power supply's output OLP/OCP function also provides protection against short circuits. When a short circuit is applied, the output current will operate in "Hiccup mode", as shown in the illustration in the OLP/OCP section on this page. The power supply will return to normal operation after the short circuit is removed.

Over Temperature Protection

As mentioned above, the power supply also has Over Temperature Protection (OTP). This is activated when the overload condition persists for an extended duration and the output current is below the overload trigger point but $>100\%$ load. In the event of a higher operating temperature condition at 100% load, the power supply will run into OTP when the surrounding air temperature is higher than the operating temperature. When activated, the output voltage will go into latch mode until the input voltage is removed; then, reapplied, and the surrounding air temperature drops to its normal operating temperature.

Power Good

Power Good+ pin is an open collector transistor (40V/600 mA rating). A resistor (suggested value 10 Kohm, 1/8 W) can be added between 5 V STANDBY pin (or, other available pull-up voltage that is no greater than 30V) and the Power Good+ pin (refer to figure below). Value of pull-up resistor may have to be adjusted, depending on voltage used, and other end-use conditions of the Power Good+ pin connection to the product. When AC input is on, Power Good+ pin will be high. When AC input is off, Power Good+ pin will be low. There will be a minimum of 5 milliseconds (at 150W load) between the time the power good goes to low level, and the time when the output reaches 90% of its rated value.




Remote On_Off/Inhibit

Remote ON_OFF/INHIBIT can be used to enable or disable only the main output. When the main output is disabled, the +5V Standby output will continue to operate. This signal can be pulled down to a low level of 0.3 volts, or shorted to DC-Return, in order for the main output to be enabled; and, floated (no connection to the signal), or pulled up to a value greater than or equal to 3 volts, in order to disable the main output.

Remote Sense

Remote sense feature can be used to compensate for the extra voltage drop on output wires that are connected from the main output terminals, to the load. With wires connected from the remote sense pins, at the same locations as the wires from the main output, the remote sense function can compensate up to 500mV voltage drop. The power supply will not be damaged if the remote sense pins are shorted, or if a reverse/inverted polarity connection is made to the load



Certificate



Delta has been certified as meeting the requirement of ISO 13485: 2003 and EN ISO 13485:2012 for the design and manufacture of switching power supply and adaptor for medical device.



In addition to a UL Total Certification Program (TCP) approved client laboratory for IEC 62368-1. Delta also has participated UL Client Test Data Program (CDTP) for IEC 60601

(September 2023, Rev. 21)