

The **TRC (TRC-LRS-35-50)** enclosure is designed to house the Mean Well **LRS-35** and **LRS-50** power supplies. Our TRC enclosure has an easily accessible cover that is removable. This indoor enclosure is ideal when a permanently installed power supply is required for your application and it meets NEMA 1 requirements.

Compliance: ETL listed to **UL STD 508A**

TRC Part #: TRC-LRS-35-50

Weight: 2.15 lbs

Dimensions: 8.43"L x 1.81"H x 4.72"W

Functional features:

- Designed for contractor installation
- Rugged NEMA 1 steel enclosure
- Integral mounting holes with (4) .25" mounting holes for surface mounting
- (4) 1/2" NPT Knockouts
- Fits Mean Well **LRS-35** and **LRS-50** power supplies

Mean Well LRS-50 shown with TRC-LRS-35-50 enclosure



Warning

To avoid electric shock, do not energize any circuits before all internal and external electrical and mechanical clearances are checked to assure that all assembled equipment functions safely and properly.

Important use notes

- This enclosure must be used with voltages below 600V
- This enclosure must be installed in accordance with the National Electrical Code, ANSI/NFPA 70, where the ambient temperature does not exceed 40°C (104°F) maximum
- This enclosure is for indoor use only

Compliance information

This enclosure is ETL listed to **UL STD 508A**

Installing Mean Well power supplies

This enclosure has been designed to house Mean Well **LRS-35** and **LRS-50** Switching Power Supplies.

- Install the required power supply using (4) provided M3x4mm mounting screws.
- Do not over tighten.
- It is recommended that these screws be secured with a workable thread lock compound such as Loctite 222MS or equivalent.

