

- Developed to maximize quality in a cost efficient design
- Excellent temperature capabilities
- 2" x 1" metal package (6-side shielded)
- Wide 4:1 input voltage range:  
9-36, 18-75 VDC
- Minimal heat development due to high efficiencies up to 93%
- Operating temperature range -40 to +85°C
- 1600 VDC I/O-isolation
- Remote On/Off and Trim function
- Protection against short circuit, overvoltage and overtemperature
- 3-year product warranty



The TEN 40WIE is rounding out Traco Power's existing 40 Watt product range. Driven by current market trends this series was developed to maximize quality and cost efficiency in one product. Due to a new design approach the TEN 40WIE thus offers a cost efficient solution with not only no concession on quality or reliability but even improved specifications compared to its predecessor. It comes in a standard 2" x 1" metal package with a 4:1 input voltage range. High efficiencies of up to 93% allow for an operating temperature range (natural convection) of -40 to +70°C without power derating (model dependent). Certified according to the latest IT standard (IEC/EN/UL 62368-1) and equipped with additional features like remote on/off function and protection against short circuit, overvoltage and over temperature the TEN 40WIE series is suitable for many industrial applications.

## Models

Order Code	Input Voltage Range	Output 1		Output 2		Efficiency typ.
		Vnom	I <sub>max</sub>	Vnom	I <sub>max</sub>	
TEN 40-2410WIE	9 - 36 VDC (24 VDC nom.)	3.3 VDC	12'200 mA			90 %
TEN 40-2411WIE		5 VDC	8'000 mA			92 %
TEN 40-2412WIE		12 VDC	3'333 mA			92 %
TEN 40-2413WIE		15 VDC	2'666 mA			93 %
TEN 40-2415WIE		24 VDC	1'666 mA			91 %
TEN 40-2422WIE		+12 VDC	1'666 mA	-12 VDC	1'666 mA	91 %
TEN 40-2423WIE		+15 VDC	1'333 mA	-15 VDC	1'333 mA	91 %
TEN 40-2425WIE		+24 VDC	833 mA	-24 VDC	833 mA	91 %
TEN 40-4810WIE		18 - 75 VDC (48 VDC nom.)	3.3 VDC	12'200 mA		
TEN 40-4811WIE	5 VDC		8'000 mA			91 %
TEN 40-4812WIE	12 VDC		3'333 mA			92 %
TEN 40-4813WIE	15 VDC		2'666 mA			92 %
TEN 40-4815WIE	24 VDC		1'666 mA			92 %
TEN 40-4822WIE	+12 VDC		1'666 mA	-12 VDC	1'666 mA	91 %
TEN 40-4823WIE	+15 VDC		1'333 mA	-15 VDC	1'333 mA	91 %
TEN 40-4825WIE	+24 VDC		833 mA	-24 VDC	833 mA	92 %

## Options

<b>TEN-HS1</b>	- Heat-sink with clamps
<b>on demand</b> (backorder with MOQ non stocking item)	- Models with factory assembled heat-sink - Models with inverse remote control

## Input Specifications

Input Current	- At no load	24 Vin models: <b>15 mA typ.</b> 48 Vin models: <b>10 mA typ.</b>
Surge Voltage		24 Vin models: <b>50 VDC max.</b> (1 s max.) 48 Vin models: <b>100 VDC max.</b> (1 s max.)
Under Voltage Lockout		24 Vin models: <b>7 VDC min. / 8 VDC typ. / 8.8 VDC max.</b> 48 Vin models: <b>15 VDC min. / 16 VDC typ. / 17.5 VDC max.</b>
Recommended Input Fuse		24 Vin models: <b>8'000 mA</b> (fast acting) 48 Vin models: <b>4'000 mA</b> (slow blow)
Input Filter		<b>Internal Pi-Type</b>

## Output Specifications

Output Voltage Adjustment		<b>-10% to +20%</b> (By external trim resistor) (15 & 24 Vout models) <b>±10%</b> (By external trim resistor) (other models) (Single models only)
Voltage Set Accuracy		Output power must not exceed rated power! <b>±1% max.</b>
Regulation	- Input Variation (Vmin - Vmax) - Load Variation (0 - 100%)  - Cross Regulation (25% / 100% asym. load)	single output models: <b>0.2% max.</b> single output models: <b>0.3% max.</b> dual output models: <b>0.5% max.</b> (Output 1) <b>0.5% max.</b> (Output 2) dual output models: <b>5% max.</b>
Ripple and Noise (20 MHz Bandwidth)	- single output  - dual output	3.3 Vout models: <b>75 mVp-p typ.</b> 5 Vout models: <b>75 mVp-p typ.</b> 12 Vout models: <b>100 mVp-p typ.</b> 15 Vout models: <b>100 mVp-p typ.</b> 24 Vout models: <b>150 mVp-p typ.</b> 12 / -12 Vout models: <b>100 / 100 mVp-p typ.</b> 15 / -15 Vout models: <b>100 / 100 mVp-p typ.</b> 24 / -24 Vout models: <b>150 / 150 mVp-p typ.</b>
Capacitive Load	- single output  - dual output	3.3 Vout models: <b>22'000 µF max.</b> 5 Vout models: <b>12'000 µF max.</b> 12 Vout models: <b>2'000 µF max.</b> 15 Vout models: <b>1'300 µF max.</b> 24 Vout models: <b>490 µF max.</b> 12 / -12 Vout models: <b>980 / 980 µF max.</b> 15 / -15 Vout models: <b>630 / 630 µF max.</b> 24 / -24 Vout models: <b>250 / 250 µF max.</b>
Minimum Load		<b>Not required</b>
Temperature Coefficient		<b>±0.02 %/K max.</b>
Start-up Time		<b>30 ms typ. / 60 ms max.</b>
Short Circuit Protection		<b>Continuous, Automatic recovery</b>
Output Current Limitation		<b>150% typ. of Iout max.</b>
Overvoltage Protection		<b>125% typ. of Vout nom.</b> (By Zener diode)
Transient Response	- Response Time	<b>250 µs typ.</b> (25% Load Step)

## Safety Specifications

Safety Standards	- IT / Multimedia Equipment	<b>EN 62368-1</b> <b>IEC 62368-1</b> <b>UL 62368-1</b>
	- Certification Documents	

All specifications valid at nominal voltage, full load and +25°C after warm-up time unless otherwise stated.

## EMC Specifications


EMI Emissions	- Conducted Emissions	EN 55032 class A (with external filter)
	- Radiated Emissions	EN 55032 class B (with external filter) EN 55032 class A (with external filter) EN 55032 class B (with external filter)
EMS Immunity	- Electrostatic Discharge	Air: EN 61000-4-2, ±8 kV, perf. criteria A Contact: EN 61000-4-2, ±6 kV, perf. criteria A
	- RF Electromagnetic Field	EN 61000-4-3, 20 V/m, perf. criteria A
	- EFT (Burst) / Surge	EN 61000-4-4, ±2 kV, perf. criteria A EN 61000-4-5, ±2 kV, perf. criteria A
	- Conducted RF Disturbances	Ext. input component: 2 x KY 220 µF // SMDJ36A (12 Vin models) 2 x KY 220 µF // SMDJ58A (24 Vin models) 2 x KY 220 µF // SMDJ120A (48 Vin models)
	- PF Magnetic Field	Continuous: EN 61000-4-6, 10 Vrms, perf. criteria A 1 s: EN 61000-4-8, 100 A/m, perf. criteria A EN 61000-4-8, 1000 A/m, perf. criteria A

## General Specifications

Relative Humidity		95% max. (non condensing)
Temperature Ranges	- Operating Temperature	-40°C to +85°C
	- Case Temperature	+105°C max.
	- Storage Temperature	-55°C to +125°C
Power Derating	- High Temperature	
Over Temperature Protection Switch Off	- Protection Mode	115°C typ. (Automatic recovery)
Cooling System		Natural convection (20 LFM)
Remote Control	- Voltage Controlled Remote	On: 3.0 to 12 VDC or open circuit Off: 0 to 1.2 VDC or short circuit Refers to 'Remote' and '-Vin' Pin 3 mA typ. -0.5 to 1.0 mA (Inverse Remote On/Off logic on demand)
	- Off Idle Input Current	
	- Remote Pin Input Current	
Switching Frequency		225 - 275 kHz (PWM) 250 kHz typ. (PWM)
Insulation System		Functional Insulation
Isolation Test Voltage	- Input to Output, 60 s	1'131 VAC
	- Input to Case, 60 s	1'131 VAC
	- Output to Case, 60 s	1'131 VAC
Isolation Resistance	- Input to Output, 500 VDC	1'000 MOhm min.
Isolation Capacitance	- Input to Output, 100 kHz, 1 V	1'500 pF max.
Reliability	- Calculated MTBF	1'245'000 h (MIL-HDBK-217F, ground benign)
Environment	- Vibration	MIL-STD-810F
	- Mechanical Shock	MIL-STD-810F
	- Thermal Shock	MIL-STD-810F
Housing Material		Copper
Base Material		Non-conductive FR4 (UL94 V-0 rated)
Potting Material		Silicone (UL 94 V-0 rated)
Connection Type		THD (Through-Hole Device)
Weight		34 g
Thermal Impedance		10.8 K/W
	- with Heat Sink	10.3 K/W
Environmental Compliance	- Reach	
	- RoHS	

All specifications valid at nominal voltage, full load and +25°C after warm-up time unless otherwise stated.

## Outline Dimensions



Dimensions in mm (inch)

Tolerances: x.x ±0.5 (±0.02)

x.xx ±0.25 (±0.01)

Pin dimension tolerance ±0.1 (±0.004)

Pinout		
Pin	Single	Dual
1	+Vin (Vcc)	+Vin (Vcc)
2	-Vin (GND)	-Vin (GND)
3	Remote On/Off	Remote On/Off
4	+Vout	+Vout
5	-Vout	Common
6	Trim	-Vout

Specifications can be changed without notice.

Rev. September 27, 2019

Page 4 / 4