

- Compact chassis mount power module in 3.48" x 1.08" package
- Wide input voltage range 90-305 VAC
- Certified according to EN 60335-1 and IEC/EN/UL 62368-6
- I/O-Isolation 4'000 VAC
- Operating temperature range -40°C to +70°C
- No load input power <0.1W (acc. ErP directive)
- High efficiency up to 88%
- Internal EN 55032 class B filter
- Protection class II prepared
- 3 year product warranty



UL 62368-1 IEC 62368-1

The TMPW 25-J is a 25 Watt AC/DC series with an extended input range of 90-305 VAC and is suitable for industrial and household/building technology applications and comes in a compact encapsulated plastic case. The 305 VAC (277 VAC ±10%) threshold is derived from a 480 VAC three-phase supply voltage often used in heavy industrial applications. Through the increased voltage level, the drawn current from the load is effectively reduced, which allows for an overall more compact and lightweight design approach. They offer an I/O-isolation voltage of 4000 VAC, a high temperature range of -40 to +70°C and are prepared for protection class II applications. Additionally, an internal EN 55032 class B filter saves valuable board space for an otherwise often mandatory external filter setup. An energy efficient design (<0.1 Watt standby power consumption) and safety approvals according to IEC/EN/UL 62368-1 and EN 60335-1 make this series suitable for a wide range of industrial and household/building technology applications.

Models				
Order Code	Output Power max.	Output Voltage nom.	Output Current max.	Efficiency typ.
TMPW 25-105-J	20 W	5.1 VDC	3'922 mA	84 %
TMPW 25-112-J	25 W	12 VDC	2'083 mA	88 %
TMPW 25-115-J		15 VDC	1'666 mA	88 %
TMPW 25-124-J		24 VDC	1'042 mA	87 %

### Input Specifications

Input Voltage	- AC Range - DC Range	90 - 305 VAC (Full Range) 100 - 250 VDC (264 VAC max. for Household Certification)
Input Frequency		47 - 63 Hz (designed to meet: 47 - 440 Hz)
Input Current	- Full Load & Vin = 230 VAC - Full Load & Vin = 115 VAC	320 mA max. 490 mA max.
Power Consumption	- At no load	100 mW max.
Input Inrush Current	- At 230 VAC - At 115 VAC	60 A max. 30 A max.
Recommended Input Fuse		2500 mA (slow blow) (The need of an external fuse has to be assessed in the final application.)

### Output Specifications

Voltage Set Accuracy		±2% max.
Regulation	- Input Variation (Vmin - Vmax) - Load Variation (0 - 100%)	1% max. 3% max. (5.1 Vout models) 2 % max. (other models)
Ripple and Noise (20 MHz Bandwidth)	5.1 VDC model: 12 VDC model: 15 VDC model: 24 VDC model:	120 mVp-p max. (w/ 0.1 µF // 47 µF) 150 mVp-p max. (w/ 0.1 µF // 47 µF) 160 mVp-p max. (w/ 0.1 µF // 47 µF) 240 mVp-p max. (w/ 0.1 µF // 47 µF)
Capacitive Load	5.1 VDC model: 12 VDC model: 15 VDC model: 24 VDC model:	2'000 µF max. 680 µF max. 220 µF max. 220 µF max.
Minimum Load		Not required
Temperature Coefficient		±0.05 %/K max.
Hold-up Time	- At 230 VAC	36 ms min.
Short Circuit Protection		Continuous, Automatic recovery
Overvoltage Protection		105 - 145% of Vout nom. (By zener diode)

### Safety Specifications

Safety Standards	- IT / Multimedia Equipment  - Household  - Certification Documents	EN 62368-1 IEC 62368-1 UL 62368-1 EN 60335-1 IEC 60335-1
Protection Class		Class II (Prepared): Reinforced Insulation
Pollution Degree		PD 2
Over Voltage Category		OVC II

### EMC Specifications

EMI Emissions	- Conducted Emissions - Radiated Emissions - Voltage Fluctuations & Flicker	EN 55032 class B (internal filter) EN 55032 class B (internal filter) EN 61000-3-3
---------------	---	--

All specifications valid at nominal voltage, full load and +25°C after warm-up time unless otherwise stated.



<b>EMS Immunity</b>	EN 55024 (IT Equipment) EN 55035 (Multimedia)
- Electrostatic Discharge	Air: EN 61000-4-2, ±8 kV, perf. criteria A Contact: EN 61000-4-2, ±4 kV, perf. criteria A
- RF Electromagnetic Field	EN 61000-4-3, 3 V/m, perf. criteria A
- EFT (Burst) / Surge	EN 61000-4-4, ±1 kV, perf. criteria A
- Conducted RF Disturbances	L to L: EN 61000-4-5, ±1 kV, perf. criteria A
- PF Magnetic Field	EN 61000-4-6, 3 Vrms, perf. criteria A
- Voltage Dips & Interruptions	Continuous: EN 61000-4-8, 1 A/m, perf. criteria A 230 VAC / 50 Hz: EN 61000-4-11 30%, 25 periods, perf. criteria A >95%, 250 periods, perf. criteria B 115 VAC / 60 Hz: EN 61000-4-11 30%, 25 periods, perf. criteria A >95%, 250 periods, perf. criteria B

### General Specifications

<b>Relative Humidity</b>	95% max. (non condensing)
<b>Temperature Ranges</b>	- Operating Temperature: -40°C to +70°C - Storage Temperature: -40°C to +85°C
<b>Power Derating</b>	- High Temperature: 2.5 %/K above 50°C (High Temperature) 2.0 %/K below -30°C (Low Temperature) - Low Input Voltage: 2 %/V below 100 VAC
<b>Cooling System</b>	Natural convection (20 LFM)
<b>Altitude During Operation</b>	5'000 m max.
<b>Insulation System</b>	Reinforced Insulation
<b>Working Voltage (rated)</b>	311 VAC
<b>Isolation Test Voltage</b>	4'000 VAC
<b>Leakage Current</b>	250 µA max.
<b>Reliability</b>	400'000 h (MIL-HDBK-217F, ground benign)
<b>Environment</b>	- Vibration: IEC 60068-2-6 2 g, 3 axis, 60 min, 10-500 Hz, 10 min/cycle - Mechanical Shock: IEC 60068-2-27
<b>Housing Material</b>	Plastic resin (UL 94 V-0 rated)
<b>Connection Type</b>	JST
<b>Weight</b>	100 g
<b>Environmental Compliance</b>	- Reach - RoHS

All specifications valid at nominal voltage, full load and +25°C after warm-up time unless otherwise stated.

## Outline Dimensions



Dimensions in mm (inch)  
Tolerances: x.x ±0.5 (±0.02)

Pinout	
Pin	Single
1	AC IN (L)
2	AC IN (N)
3	-Vout
4	NC
5	+Vout

NC: Not connected

JST housing: PSIP-03V-LE-A  
JST crimp terminals: SPSI-41T-M1.1  
SPS1-001T-M1.1